Method and device for monitoring a moving fabric web

The invention relates to a method and a device for
5   monitoring a moving fabric web, at least a part of the
width of the fabric web being detected.

A device is known from DE 101 23 870 for the automatic
monitoring of in particular textile fabrics or woven fabric
10   webs, this device being arranged directly on the production
machine of the fabric or woven fabric web. In the case of
this device, several very small sensors are arranged having
direct contact with the fabric. The device is attached to
the production machine via a vibration-damping suspension,
15   so that a transfer of the machine movement only takes place
via the textile fabric.

Although in the case of this device the woven fabric web or
the textile fabric is in direct contact with the sensor or
20   its covering glass, faults can occur in imaging of the
fabric by the sensor, for example displacements of image
sections in relation to one another, which result in the
image of the fabric no longer corresponding to the
original. In these circumstances it is then difficult to
25   detect faults in the fabric with certainty, since warp or
weft threads, for example, in a woven fabric are no longer
equidistant in the image.

The invention as characterized in the claims thus achieves
30   the object of producing a method and a device for
monitoring moving fabric webs with at least one sensor
strip, which maintains the geometrical ratios between the
individual elements from which the fabric web is

constructed as far as possible in the image of the fabric web also.

This is achieved in that on the one hand, an image of at least a part of the fabric web is produced, and on the other hand the movement of the fabric web is detected in the same part of the fabric web. From the image of the fabric web a first signal is generated, and in the same part of the fabric web the movement of the fabric web is detected and a second signal generated. The first and second signal are offset in a suitable manner in order to maintain in the image also the geometrical ratios existing in the fabric web between the individual elements that together produce the image.

In a device suitable for this, a sensor strip for scanning the fabric web seen in the direction of the width of the fabric web can be arranged at an acute angle, so that information regarding a characteristic connected with the movement of the fabric web can be derived from the signal of the same sensor strip. An image of the fabric web in the relevant part is also to be produced from the same signal, this image being built up line-wise or section-wise. However, the sensor strips can also be oriented perpendicular to the movement of the fabric web and at least one further sensor for detecting a characteristic connected with the movement of the fabric web can be arranged in the area of this part of the fabric web. A further sensor of this kind is preferably an optical sensor with one or more scanning lines.

This method and this device are used in the most common application for detecting faults in the fabric web, such as differences in the structure, colour or from patterns on the fabric web, signalling these or triggering

further actions such as stopping of the fabric web, for example. A particularly important characteristic connected with the movement of the fabric web is its momentary speed, which then applies precisely when an image of a section of

5   the fabric web is recorded or produced.

The advantages achieved by the invention are to be seen in particular in the fact that, from the signals of the sensor strip and the possibly additional signals that a further

10   sensor emits, the geometrical ratios between individual elements of the fabric web, such as between adjacent warp and weft threads in a woven fabric, for example, can be maintained even in the image of the woven fabric produced from signals of the sensor strip. It is easier and also

15   more reliable for example to correct these geometrical ratios starting out from a momentary speed instead of from an averaged speed. The further sensor can also only detect distances, in that it emits a pulse after fixedly predetermined distances covered, for example, or if

20   supplied externally with clock pulses it outputs the distances covered per clock interval by the fabric web. With the distance signal and with the signal from the sensor strip, graphic patterns or structures of the fabric web can be reproduced correctly and without distortion in

25   the image due to suitable offsetting of both signals, so that interruptions of these patterns or of the structure can also be detected correctly in the monitoring.

The invention is explained in greater detail below with

30   reference to an example and to the enclosed figures.

Fig. 1 shows a first diagrammatic representation of an arrangement according to the invention of sensor strips and further sensors ahead of a fabric web,

Figs. 2, 3, 5 and 6 each show a further arrangement of sensor strips,

Fig. 4 shows an arrangement according to Fig. 1 with further elements,

Fig. 7 shows a distance – time diagram for a fabric web,

Fig. 8 shows a diagrammatic representation of the geometrical ratios on scanning of a fabric web and

Fig. 9 shows a signal such as is possibly generated by sensor strips according to Fig. 2.

Fig. 1 shows ahead of a fabric web 1, the edges of which are indicated by lines 2 and 3, sensor strips 4a, 4b, 4c, which are formed identical to one another, as well as further sensors 5a, 5b, 5c, which detect a characteristic of the fabric web that is connected with the movement of the fabric web 1. Such characteristics are for example the distance that the fabric web 1 covers, the momentary speed of the fabric web 1 in the direction in which it is moving, the acceleration in the event of changes of speed, etc. Each sensor strip 4 and each further sensor 5 are arranged so that they traverse a part of the fabric web 1 when this moves in the direction of an arrow 6 (Fig. 3). Such parts 7a, 7b, 7c of the fabric web 1 are delimited in Figure 1 by further lines 8a, 8b inside the fabric web 1. The sensor strips 4a and 4c and any further sensor strips present and not shown here form a first sensor line 20, while the sensor strip 4b, alone or together with possible further sensor strips not shown here, forms a second sensor line 21, which runs parallel to the first sensor line 20.

The sensor strips 4a and 4c from the first sensor line 20
and the sensor strip 4b from the adjacent second sensor
line 21 partly overlap seen in the direction of movement of
the fabric web.

5

Fig. 2 shows a further arrangement of sensor strips 9a,
9b, 9c and possible further sensors 10a, 10b, 10c, the
sensor strips 9 being inclined by an angle α, which here
for example is 15°, towards a line 11 that extends in the
10   direction of the width of the fabric web 1, perpendicular
to the direction of the arrow 6.

Fig. 3 shows an arrangement of sensor strips 12a, 12b, 12c
according to Fig. 1, but with further sensors 13a and 13b,
15   which can each be assigned to two sensor strips, as well as
further sensors 13c and 13d, which are only assigned here
to one sensor strip. The further sensors 13a and 13b are
arranged in the edge areas of the sensor strips 12. It
should be noted here that the arrangements shown with three
20   sensor strips have been chosen arbitrarily and are only to
be interpreted as examples. Naturally any number of sensor
strips 12 can be arranged, the greater the width the more
sensor strips, to detect the entire width of the fabric
web 1. This applies to all arrangements shown in Figures 1.
25   to 6. However, it is the case in particular for the
arrangement according to Fig. 3 that two further sensors
are assigned in each case to the sensor strips 12. For
example, the further sensors 13a and 13b are assigned to
the sensor strip 12b. Further sensors 13a and 13c are
30   assigned to the sensor strip 12c. Further sensors 13b
and 13d are assigned to the sensor strip 12c. The sensor
strips 12 are arranged together with the further sensors in
a housing 18, which also has suitable lighting for the

fabric web 1 if no light source is integrated into the
sensor strips.

Fig. 4 shows an arrangement of the sensor strips 4a – 4c as
5 already known from Fig. 1. In contrast to that, however,
the further sensors 5a – 5c are no longer connected
upstream of the sensor strips 4, but downstream. This is
measured against the direction of movement of the fabric
web 1 as indicated by the arrow 6. Lines 14a, 14b and 14c
10 connect the sensor strips 4 and the further sensors 5 to a
processor 15a, 15b, 15c respectively, which are connected
via lines 16a, 16b, 16c to an input/output device 17. Thus
several sensor strips and several further sensors are
assigned to a common input/output device 17. An output 19
15 on the input/output device 17 serves for example as a
connection to a computer, such as a so-called PC, to which
several devices according to the invention can be
connected.

20 Fig. 5 shows an arrangement of five sensor strips 22, 23,
24, 25 and 26, the sensor strips 22, 24 and 26 forming a
first sensor line 27 and the sensor strips 23 and 25
forming a second sensor line 28. A further sensor 29 is
assigned here only to the sensor strip 24 and detects a
25 part of the fabric web that is also detected by the sensor
strip 24, the sensor strip 24 and the further sensor 29 not
scanning the fabric web according to the same criteria or
detecting the same features therein.

30 Fig. 6 shows a further arrangement with five sensor
strips 30, 31, 32, 33 and 34 and five further sensors 35,
36, 37, 38 and 39. Here the further sensors are arranged
respectively adjacent to the sensor strips for which they

supply no movement indication. Thus the further sensors are connected seen in the direction of movement of the fabric web 1 alternately upstream and downstream of the assigned sensor strips. For example, the further sensor 35

5 is connected downstream of the relevant sensor strip 30, while the further sensor 36 is connected upstream of the relevant sensor strip 31, or vice-versa. This arrangement makes it possible to fit the sensor strips and the further sensors in a particularly space-saving arrangement.

10 Fig. 7 shows a distance-time diagram, for example for the fabric web 1, a line 40 indicating the distance covered per unit of time by the fabric web 1 with always ideal, uniform movement of the fabric web 1. Thus values for the distance

15 covered can be entered along one axis 42 and values for the time along an axis 41. A curve 43 represents the distance actually covered by the fabric web at different times, which distance is produced by the uneven movement of the fabric web in the area of the sensor strips and further

20 sensors.

Fig. 8 shows in a diagrammatic representation the ratios as they appear with the arrangement of an inclined sensor strip as shown in Fig. 2. 44 here denotes a section

25 through a group of weft threads of a woven fabric that is moving in the direction of an arrow 45. Slewed by 90° in comparison with the section 44, the centre lines or axes of these weft threads are drawn in with horizontal lines 46, the warp threads or their influence on these centre lines

30 or axes and thus the weaves being left out here to make the representation simpler. A sensor strip 47 is represented here only by those discrete elements that can detect picture elements from the fabric web. The sensor strip 47

here is an optical sensor with a single scanning line. A coordinate system characterizes further an X-axis corresponding to the width of the fabric web and a Y-axis corresponding to the direction of movement of the fabric
5   web 1.

Fig. 9 shows a first signal 48 and a second signal 49 such as a sensor strip can emit when it detects a woven fabric. Both signals 48, 49 are recorded over a time axis T and
10   next to an axis V, the axis V indicating the amplitude of the signal from the sensor strip, which is expressed for example by an electric voltage.

The mode of operation of the invention is as follows:
15   While for example one sensor strip 4a (Fig. 4) scans the part 7a of the fabric web 1 and maps this onto picture elements and converts it into intensity values, or into grey scale and colour values, which are stored in the memory of the processor 15a, the further sensor 5a
20   continuously emits a signal to the processor 15a, which represents for example the momentary movement of the part 7a of the fabric web 1 in the area of the sensor strip 4a. The further sensor 5a traverses a section inside the part 7a of the fabric web 1. This applies likewise to
25   the further sensors 5b, 5c and the parts 7b, 7c of the fabric web 1. The processors 15 contain a program in the program memory that recognizes periodicities or projecting signal portions from the signal of the sensor strip and processes these together with the signal from the further
30   sensor. The aim of this program is to form a clearly structured signal or a clear image from the signal of the sensor strip. The object should thus for example be achieved that in an image that can be composed from the

picture elements in the data memory of a processor 15, in a
textile fabric the geometrical relationships between the
individual yarns or threads are preserved such that they
correspond to those of the actual fabric.   In the case of

5   woven fabrics, the structure from the warp threads and the
weft threads should thus be made clearly recognizable.
Original distances or geometrical ratios between warp and
weft threads of a woven fabric or between threads of a knit
fabric should be reproduced in the image.   Due to the

10   further sensors arranged as closely as possible to and in
the working area of the sensor strips on the fabric web 1,
it is possible to detect even local movements that are
different in the individual parts 7a - 7c, such as e.g.
distortion, and to compensate for them, i.e. to ensure that

15   the effect of the distortion does not geometrically distort
the image from the sensor strip.   In particular, the
further sensors 5, 10, 13, 29, 35 - 39 detect the movement
of the fabric web 1 as shown for example in Fig. 7.   From
this it is recognized that the fabric web does not always

20   cover identical distances per unit of time.   Thus the
images that the sensor strips 4, 9, 12 and 22 - 26 detect
can even contain not always the same number of elements
such as threads, weft threads, etc.   If this image
information is combined with the signal relating to the

25   movement for example from the further sensor, a faithful
image of the fabric web can be produced even if its
movement is uneven.

If no further sensor is used and if a characteristic

30   connected with the movement of the fabric web is to be
detected by the sensor strip alone, then the latter must be
inclined by an angle α, as shown in Fig. 2.   The movement
of the fabric web can be detected as shown with reference

to Figures 8 and 9. As an example, we are assuming here
that the fabric web has a three-dimensional structure such
as applies to textile fabrics, and that it moves in the
direction of an arrow 45. If we look at the movement of a
5   single weft thread 50, which is also represented by its
centre line or axis 51, then a curve is produced for
example for the intensity of light that is reflected at
this or absorbed by this, corresponding to a signal 48
(Fig. 9). The signal 48 is produced in particular by a
10   point or a surface line 52 of the weft thread 50, which is
also represented by the centre line 51, passing by a sensor
element 53, the sensor element 53 being able to generate a
picture element, meaning that in this picture element the
intensity progresses corresponding to the signal 48. If a
15   short time later the weft thread 50 reaches a place (shown
here moved forward for greater clarity) in the direction of
the arrow 45 as designated by 54, which corresponds to a
position of the centre line corresponding to a dashed
line 55, then an adjacent sensor element 56 detects this
20   weft thread in its position 54, a signal 49 according to
Fig. 9 being produced, which is delayed by a time Δt
relative to the signal 48. However, since a distance ΔL
between the sensor elements 53 and 56 or centre lines 51
and 55 is known, the momentary speed v of the fabric web 1
25   is found according to the formula $v = \Delta L / \Delta t$. However, it
is also possible to calculate from this even the
acceleration, for example, as another characteristic that
is connected with the movement of the fabric web.

30   The movement of the fabric web 1 or a characteristic
connected with the movement of the fabric web can also be
ascertained from the overlapping sensor strips, as shown
for example in Fig. 3. In the overlapping area of the

sensor strips 12a and 12b, which is located before and after the further sensor 13a that is drawn in here but not required in this case, the same parts of the fabric web 1 are detected and thus comparable signals produced, which

5   occur, however, with a delay that corresponds to the distance between the two sensor strips 12a and 12b divided by the speed of the fabric web 1 in this area. Since the distance is known and the delay can be determined from both signals, the speed can be calculated from this.

10

Sensors known by the designation "contact type image sensor", for example, such as are installed in a flatbed scanner or a fax machine for scanning a piece of paper supplied, can be used as sensor strips 7, 9, 12. In this

15 case the sensors can contact the fabric web directly, or they are covered by a cover plate for example of glass, which is touched by the fabric web. A small air gap can also separate the fabric web and the sensor from one another. It is possible also to use surface cameras or

20 line cameras instead of the said contact sensors or sensor strips, which cameras then scan a rather larger area of the fabric web seen in the direction of the arrow 6. The further sensor 5, 10, 13 can be a sensor such as is known for example by the name "CMOS Active Pixel Image Sensor"

25 supplied by National Semiconductor. Even a further sensor such as supplied by Agilent Technologies under the name ADNS-2051 Optical Mouse Sensor can be used.